

TIMING BELT PULLEYS

5 MM PITCH

FOR BELT 9 MM WIDE

Tooth Profile

HTD® SERIES



Material: Aluminum Alloy. **Dimensions in inches.** For pure metric - please inquire.
Finish: Anodized. **See QX-A1 series for 5MM pitch HTD belts.**

Cat. No.	No. of Grooves	Bore +.001 -.000 A	Pitch Diameter	O.D. * B	Flange O.D. ±1/64 C	Face Width D	Overall Length ± 1/64 E	Hub Diameter ± 1/64 F	Hub Proj. G
FQA-F2-12 FQA-F3-12	12	.250	.752	.707	7/8	35/64	51/64	7/16	1/4
FQA-F2-13 FQA-F3-13	13		.815	.770	15/16			1/2	
FQA-F2-14 FQA-F3-14	14		.877	.832	1			9/16	
FQA-F2-15 FQA-F3-15	15		.940	.895	1-1/16				
FQA-F2-16 FQA-F3-16	16		1.008	.958	1-3/32			5/8	
FQA-F2-17 FQA-F3-17	17	.250	1.065	1.020	1-3/16	35/64	51/64	11/16	1
FQA-F2-18 FQA-F3-18	18		1.128	1.083	1-1/4			3/4	
FQA-F2-19 FQA-F3-19	19		1.191	1.146	1-5/16				
FQA-F2-20 FQA-F3-20	20		1.253	1.208	1-3/8			13/16	
FQA-F2-22 FQA-F3-22	22		1.379	1.334	1-1/2				
FQA-F2-24 FQA-F3-24	24	.250	1.504	1.459	1-5/8	35/64	55/64	1	5/16
FQA-F2-25 FQA-F3-25	25		1.566	1.521	1-11/16			1-1/16	
FQA-F2-26 FQA-F3-26	26		1.629	1.564	1-3/4				
FQA-F2-28 FQA-F3-28	28		1.754	1.709	1-7/8			1-1/4	
FQA-F2-30 FQA-F3-30	30		1.880	1.835	2				
FQA-F2-32 FQA-F3-32	32	2.005	1.960	2-1/8					
FQA-F2-34 FQA-F3-34	34	2.130	2.085	2-1/4					
FQA-F3-36 FQA-F3-38 FQA-F3-40	36 38 40	.3125	2.256 2.381 2.506	2.211 2.336 2.461	-		15/16	1-1/2	25/64

O.D. Tolerances - 12-16 grooves +.002, -.000

17-32 grooves +.003, -.000 34-40 grooves +.004, -.000

12,13 grooves - 1 set screw

14-40 grooves - 2 set screw @ 90°

53F (800) 243-0986
In CT (203) 775-4877

HTD® Trademark Gates

NORDEX